

CASES 1200 Case



1200 Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Unconditional Lifetime Guarantee of Excellence

1200 Case Configurations

Cat. #	Description
1200	1200 Case
1200NF	1200 Case (No foam)



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1200 Case Specifications

Exterior Dimensions (L x W x D)

10.62" x 9.68" x 4.87" (27 x 24.6 x 12.4 cm)

Interior Dimensions (L x W x D)

9.25" x 7.12" x 4.12" (23.5 x 18.1 x 10.5 cm)

Lid Depth

1.18" (3 cm)

Bottom Depth

2.93" (7.4 cm)

Total Depth

4.11" (10.4 cm)

Weight with Foam

2.87 lbs. (1.3 kg)

Weight without Foam

2.65 lbs. (1.2 kg)

Buoyancy Max.

12.02 lbs.
(5.45 kg)

Range Temperature

-10 / 210° F
(-23 / 99° C)

1200 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1200 Case Accessories

Cat. #	Description
1200PF	Special Application Panel Frame
1201	3 pc. Replacement Foam Set
1203	Replacement O-ring

Pelican Stockists - Queensland Australia



Qld Protective Cases

Unit 5 / 1 Pinnacle Street, Brendale QLD 4500

Phone: 07 3881 2358

Email: sales@qldprocases.com.au

Website: www.qldprocases.com.au