



1450 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Unconditional Lifetime Guarantee of Excellence

1450 Case Configurations

Cat. #	Description
1450	1450 Case
1450NF	1450 Case (No foam)
1454	1450 Case with Padded Dividers



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1450 Case Specifications

Exterior Dimensions (L x W x D) 16.00" x 13.00" x 6.87" (40.6 x 33 x 17.4 cm)	Interior Dimensions (L x W x D) 14.62" x 10.18" x 6.00" (37.1 x 25.8 x 15.2 cm)	
Lid Depth 1.75" (4.4 cm)	Bottom Depth 4.25" (10.8 cm)	Total Depth 6.00" (15.2 cm)
Weight with Foam 6.39 lbs. (2.9 kg)	Weight without Foam 5.51 lbs. (2.5 kg)	Buoyancy Max. 30 lbs. (13.61 kg)

Range Temperature

-10 / 210° F
(-23 / 99° C)

Personalized Nameplate Available

1450 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280

1450 Case Accessories

Cat. #	Description
1450PF	Special Application Panel Frame
1451	3 pc. Replacement Foam Set
1453	Replacement O-ring
1455	Padded Divider Set Only
1500IP	Instapak Quick® RT

Pelican Stockists - Queensland Australia



Qld Protective Cases

Unit 5 / 1 Pinnacle Street, Brendale QLD 4500

Phone: 07 3881 2358

Email: sales@qldprocases.com.au

Website: www.qldprocases.com.au