

CASES

# 1460 Case



### 1460 Case

- Top lid opens up to 180° for on-the-field anti-roll stability when open
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handles
- Stainless steel hardware and padlock protectors
- Pick N Pluck™ foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence
- [Also available with EMS Organizer and Dividers](#)
- Watertight, crushproof, and dust proof

### 1460 Case Configurations

Cat. #	Description
1460	1460 Case
1460NF	1460 Case (No foam)
1460AALG	1460 Case (with custom foam for 9430/9435)



Black



OD Green\*



Desert Tan

\*OD Green available upon request (minimum quantities apply)

### 1460 Case Specifications

#### Exterior Dimensions (L x W x D)

20.85" x 12.73" x 12.75" (52.9 x 32.3 x 32.4 cm)

#### Lid Depth

4.91" (12.5 cm)

#### Weight with foam

12.48 lbs. (5.66 kg)

#### Range Temperature

-40 / 210° F  
(-40 / 99° C)

### 1460 Case Certificates

- IP67 (1 meter submersion for 30 minutes)

### 1460 Case Accessories

Cat. #	Description
1461	Replacement Foam Set
1463	Replacement O-ring

#### Interior Dimensions (L x W x D)

18.54" x 9.92" x 10.92" (47.1 x 25.2 x 27.7 cm)

#### Bottom Depth

6.01" (15.3 cm)

#### Weight without foam

8.75 lbs. (3.97 kg)

#### Total Depth

10.92" (27.7 cm)

#### Buoyancy Max.

82 lbs.  
(37.19 kg)

**Pelican Stockists - Queensland Australia**



**Qld Protective Cases**

Unit 5 / 1 Pinnacle Street, Brendale QLD 4500

Phone: 07 3881 2358

Email: [sales@qldprocases.com.au](mailto:sales@qldprocases.com.au)

Website: [www.qldprocases.com.au](http://www.qldprocases.com.au)