

CASES 1560 Case



1560 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded top and side handles
- Stainless steel hardware and padlock protectors
- 2 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Unconditional Lifetime Guarantee of Excellence
- **Retractable extension handle**
- **Strong polyurethane wheels with stainless steel bearings**

1560 Case Configurations

Cat. #	Description
1560	1560 Case
1560NF	1560 Case (No foam)
1564	1560 Case with Padded Dividers



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1560 Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
22.06" x 17.93" x 10.43" (56 x 45.5 x 26.5 cm)	20.37" x 15.43" x 9.00" (51.7 x 39.2 x 22.9 cm)	
Lid Depth	Bottom Depth	Total Depth
2.00" (5.1 cm)	7.00" (17.8 cm)	9.00" (22.9 cm)
Weight with Foam	Weight without Foam	Buoyancy Max.
20 lbs. (9.07 kg)	17 lbs. (7.71 kg)	104 lbs. (47.17 kg)
Range Temperature	No. of Wheels	
-10 / 210° F (-23 / 99° C)	2	

Personalized Nameplate Available

1560 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1560 Case Accessories

Cat. #	Description
0343	Replacement O-ring
1550IP	Instapak Quick® RT
1561	4 pc. Replacement Foam Set
1562	Pick 'N' Pluck™ Sections Only (set of 2)
1565	Padded Divider Set Only
1569	Lid Organizer for 1560 Case

Pelican Stockists - Queensland Australia



Qld Protective Cases

Unit 5 / 1 Pinnacle Street, Brendale QLD 4500

Phone: 07 3881 2358

Email: sales@qldprocases.com.au

Website: www.qldprocases.com.au