

LIGHTS
1800
PeliLite



PeliLite™ 1800 Flashlight

This one is built to last. The unbreakable ABS body resists chemicals, water and corrosion. The polycarbonate lens and focused Xenon lamp module produce a tight white beam that penetrates smoke and fog. The PeliLite 1800 flashlight is submersible, thanks to the o-ring seal and twist-on shroud that eliminates leaky switches. It is powered by 2 C alkaline cells.

Minimum Pack 6 ea.
Packaged Weight: 3.8 oz.



Submersible

NSN List

NSN #	Description
6230-01-365-7648	1800 Orange
6230-01-465-5045	1800C Black

PeliLite™ 1800 Flashlight Configurations

Cat. #	Description
1800	PeliLite™ 1800 Flashlight (Carded)



PeliLite™ 1800 Flashlight Specifications

Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
Xenon	15.0	5300

Batteries	Battery Burn Time	Battery Pack/Charging Time
2 C Alkaline (Not included)	8 hrs.	N/A

Watts	Voltage
2.2	3

Length	Weight w/Batteries	Weight w/o Batteries
6" (15.2 cm)	7.8 oz. (0.22 kg)	2.9 oz. (0.08 kg)

PeliLite™ 1800 Flashlight Approvals

	Class I, Div. 2; Gp ABCD, T3C / Class II; Div. 2; Gp G.
	Class I, Div. 2; Gp. ABCD / Class II; Div. 2; Gp. G; T4
	Listed 4S67/E184884 Class I, Div. 2; Gp. D / Class I; Zone 2; Gp. IIA; T3
	10C-628-0

PeliLite™ 1800 Flashlight Accessories

Cat. #	Description
1804	PeliLite™ 1800 Xenon Lamp Module

Pelican Stockists - Queensland Australia



Qld Protective Cases

Unit 5 / 1 Pinnacle Street, Brendale QLD 4500

Phone: 07 3881 2358

Email: sales@qldprocases.com.au

Website: www.qldprocases.com.au