

Uncontrolled document as of April 8, 2011. Refer to website for up to date specifications.



9430SL Spot Light Remote Area Lighting System

Two years ago we introduced the 9430 Remote Area Lighting System and changed the way we light our work. Pelican continues to lead the industry: The new Spot Beam and Infrared Beam models save lives and defeats enemy threats.

With a tight, 10° beam, the new 9430SL (Spot Light) reaches hundreds of yards for effective search and rescue, law enforcement and military operations. And with a run time of up to 15 hrs, the 9430SL will outlast the longest night of the year.

The 9430IR (Infrared) enhances Night Vision optics to provide improved visibility in complete darkness. With a low thermal signature, the 9430IR is perfect for covert surveillance.

The 9430 RALS family: searching, defending and illuminating a moonless night near you.

9430SL Spot Light Remote Area Lighting System Configurations

Cat. #	Description
9430SL	9430SL Spot Light Remote Area Lighting System



9430SL Spot Light Remote Area Lighting System Specifications

Light Source

LED Type High Flux LED	LED Life 50000 hrs.	Tested Lumen Value 1000 (Low) 2000 (High)
----------------------------------	-------------------------------	--

Lamp Heads 1	Number of LEDs 24 LEDs per head	Beam Spread 10°
------------------------	---	---------------------------

Brightness Settings 2

Power Source

Battery Type 12v Rechargeable, Sealed	Battery Burn Time 15 hrs. (Low) 8 hrs. (High)	Battery Charging Time 5 hrs. from full discharge
---	--	--

Battery Life 500 cycles	Low Battery Warning Intermittent Blinking	12V Primary Sockets 1
-----------------------------------	---	---------------------------------

12V Auxiliary Sockets 1	Watts 24	Voltage 12
-----------------------------------	--------------------	----------------------

Dimensions & Weight

Head Length 6.5" (16.5 cm)	Head Width 7.87" (20 cm)	Head Depth 2.56" (6.5 cm)
Width Closed 7.87" (20 cm)	Length Closed 15.75" (40 cm)	Height Closed 9.06" (23 cm)
Mast Height Extended 32.28" (82 cm)	Cord Length (Retracted) 13.78" (35 cm)	Weight 22.05 lbs. (10 kg)

9430SL Spot Light Remote Area Lighting System Approvals

RoHS (Restriction of Hazardous Substances) Compliant
CE Approval: Approved
CE Certificate: Yes

9430SL Spot Light Remote Area Lighting System Accessories

Cat. #	Description
1460AALG	1460 Case (with custom foam for 9430/9435)
9438	9430 RALS Universal Charger
9437	Extension Cord 118 inches (3m)
9431	9430 Tear-Off Back Pack
9430T	9430T Tripod Kit
9432	9430 Back Pack

Pelican Stockists - Queensland Australia



Qld Protective Cases

Unit 5 / 1 Pinnacle Street, Brendale QLD 4500

Phone: 07 3881 2358

Email: sales@qldprocases.com.au

Website: www.qldprocases.com.au